Flexible and Expandable Ringlock System Scaffolding for Construction





Product Specification

• Brand Name:

Standard:	EN12810 & EN12811
Max Height:	≤30m
Safety Factor:	≥4
Vertical Adjustment:	≤±3°
Material:	Q235 Steel
Joints:	Double-locking
Components:	Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc.
Vertical Load Capacity:	≥45KN
Highlight:	Expandable Ringlock System Scaffolding, Construction Ringlock System Scaffolding, Construction HDG Ringlock

Bythai Scaffolding Co.,Ltd

bythaiscaffold.com



BY THAI

Product Description:

Ringlock system scaffolding is a safe and reliable formwork system that provides excellent vertical and horizontal load capacity with a safety factor of ≥ 4 . This system is certified to meet EN12810 and EN12811 standards, and offers a vertical load capacity of ≥ 45 KN and a horizontal load capacity of ≥ 15 KN. Moreover, its horizontal adjustment capability is $\leq \pm 3^{\circ}$, making it a versatile and reliable choice in many scenarios. The Ringlock formwork provides a quick and easy installation process and is highly durable, making it the ideal choice for all kinds of construction projects.

Features:

Product Name: Ringlock System Scaffolding Warranty: 2 Years Horizontal Adjustment: ≤±3° Weight: ≤30kg/m2 Surface Treatment: Hot-dip Galvanized Max Height: ≤30m

Applications:

Bythai BT03 Ringlock System Scaffolding is an ideal solution for construction and engineering projects. It is equipped with vertical load capacity of \geq 45KN, safety factor of \geq 4 and lightweight of \leq 30kg/m2. With a size of 48.3mm and maximum height of \leq 30m, this product is the perfect choice for scaffolding. It is composed of high quality ringlock accessories and scaffolding ringlock standard. It offers a reliable and secure scaffolding system with excellent support.

Customization:

Bythai's Ringlock System Scaffolding: Customized Service

Brand Name: Bythai Model Number: BT03 Place of Origin: China Max Height: ≤30m Material: Q235 Steel Horizontal Adjustment: ≤±3° Components: Vertical, Horizontal, Diagonal, Brace, Base Plate, Ladder, Etc. Weight: ≤30kg/m2 Bythai's Ringlock System Scaffolding is the ideal choice for your construction projects. Our Ringlock System is designed for maximum safety and convenience, and is perfect for any size project. This system is made of high-quality Q235 steel and has a maximum height of ≤30m, a horizontal adjustment of ≤±3°, and a weight of ≤30kg/m2. Components include vertical, horizontal, diagonal, brace, base plate, ladder, etc. Our Ringlock andamios are the perfect solution for any construction project.

Support and Services:

Ringlock System Scaffolding Technical Support and Service

At Ringlock System Scaffolding, our mission is to provide the very best in Technical Support and Service. We are committed to delivering the highest quality support to our customers, and are proud to offer the following services:

24/7 customer service and technical support

Free online tutorials and videos to help you get the most out of your Ringlock System Scaffolding products

Onsite installation and repairs

Live chat support

Free product evaluation and advice

Warranty services

We understand that our customers have different needs and budgets, so we offer a range of services to fit any budget. Whether you need basic technical support or full-service installation and repairs, we are here to help.

At Ringlock System Scaffolding, we are committed to providing the best customer service and technical support in the industry. If you have any questions or need assistance, please don't hesitate to contact us. We look forward to helping you get the most out of your Ringlock System Scaffolding products!

Packing and Shipping:

Ringlock System Scaffolding Packaging and Shipping

Ringlock system scaffolding is a safe and efficient scaffolding system. It is widely used in construction, bridge and tunnel projects.

Packaging

Ringlock system scaffolding is usually packed in bundles, with each bundle containing a set of components. Each bundle is labeled with the product name and model number, so that the components can be easily identified. The bundles are then placed in cardboard boxes, with the necessary accessories for assembly.

Shipping

The bundles of Ringlock system scaffolding are usually shipped by truck or train, depending on the distance and size of the order. The packages are carefully and securely loaded onto the truck or train, to ensure the safety of the components during transit. The packages are then transported to the destination, where they are unloaded and delivered to the customer.

